



Kod
H07VVH6-F CU/PVC/PVC
CU: IEC 60228 SINIF 5
F: Fleks iletken

Standartlar
TS IEC 60227-6 71F

Teknik Veriler
Maksimum çalışma sıcaklığı : 70 °C
Maksimum kısa devre sıcaklığı : 160 °C (max. 5 sn.)
Anma gerilimi : 450/750 V

Kullanıldığı Yerler
Asansör ve yürüyen merdivenlerde kontrol kablosu ,
vinçlerde ve dalgiç pompalarında güç kablosu olarak
kullanılır.

Yapısı
1. İnce çok telli bükülgen bakır iletken
2. PVC izole
3. PVC kılıf

Code
H07VVH6-F CU/PVC/PVC
CU: IEC 60228 CLASS 5
F: Flex copper conductor

Standards
IEC 60227-6 71F

Technical Data
Max. operating temperature : 70 °C
Short circuit temperature : 160 °C (max. 5 sec.)
Rated voltage : 450/750 V

Application
Used as control cables in lifts, elevators also as power cables in
cranes and submersible pumps.

Construction
1. Flexible wires with fine stranded copper conductors
2. PVC insulation.
3. PVC sheath

BOYUT VE AĞIRLIKLAR (DIMENSIONS AND WEIGHTS)				ELEKTRİKSEL ÖZELLİKLER (ELECTRICAL PROPERTIES)	
Type Tip	Nominal Kesit Nominal cross- section	Dış Çap(yaklaşık) Overall Diameter (approx.)	Net Ağırlık(yaklaşık) Net Weight(apprx.)	İletken DC Direnci 20 °C'de max. DC Conductor Resistance at 20 °C	Akım taşıma kapasitesi Current Carrying Capacity
	mm ²	mm	kg/km	ohm / km	Havada 30 °C'de In Air at 30 °C A
H07VVH6-F	3X1,5	5,10X11,67	107,38	13,3	16
	3X2,5	5,91X13,91	156,62	7,98	20
	3X4	6,45X16,71	213,79	4,95	25
	3X6	7,01X18,51	288,87	3,30	33
	3X10	9,41X24,55	509,75	1,91	45
	3X16	10,69X28,55	714,97	1,21	61
	3X25	13,33X33,56	1093,63	0,780	80
	3X35	14,30X36,85	1358,6	0,554	103
	3X50	16,22X42,85	1814,23	0,386	120
	3X70	19,47X48,82	2740,49	0,272	152
	3X95	21,08X55,80	3318,44	0,206	184
	3X120	21,80X59,00	4529,02	0,161	212
	3X150	23,00X62,20	5440,73	0,129	-
	3X185	25,10X68,50	6656,43	0,106	-
	3X240	27,90X76,50	8385,94	0,0801	-
	4X1,5	5,78X15,96	157,73	13,30	16
	4X2,5	5,87X18,84	218,75	7,98	20
	4X4	6,66X20,79	282,89	4,95	25
	4X6	7,41X23,24	352,44	3,30	33
	4X10	9,87X31,55	684,78	1,91	45
	4X16	10,20X33,00	950,00	1,21	61
	4X25	12,00X40,00	1370,15	0,780	80
	4X35	13,80X45,80	1859,90	0,554	103
	4X50	15,80X54,80	2602,44	0,386	120
	4X70	17,80X60,80	3447,46	0,272	152
	4X95	19,80X70,80	4581,96	0,206	184
	4X120	20,70X72,80	5840,65	0,161	212
	4X150	23,00X81,40	7203,52	0,129	-
	4X185	25,10X89,80	8819,82	0,106	-
	4X240	27,90X100,40	11116,98	0,0801	-